



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 030 240 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

23.08.2000 Bulletin 2000/34

(51) Int. Cl.<sup>7</sup>: G06F 3/147

(21) Application number: 00300492.6

(22) Date of filing: 24.01.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 17.02.1999 US 250858

(71) Applicant:

NCR INTERNATIONAL INC.  
Dayton, Ohio 45479 (US)

(72) Inventors:

- Kato, Shuzo  
Kanagawa 254-0902 (JP)
- Utsumi, Yoshitaka  
Kanagawa 256-0802 (JP)
- Takagi, Osamu  
Kanagawa 250-0055 (JP)

(74) Representative:


Williamson, Brian et al  
International IP Department,  
NCR Limited,  
206 Marylebone Road  
London NW1 6LY (GB)

### (54) Electronic price label battery storage apparatus and replacement method

(57) An electronic price label battery storage apparatus and replacement method which maintains power to a memory within the electronic price label during removal and replacement of batteries. The battery storage apparatus includes a first electrical contact for simultaneously providing a first electrical path to first polarity sides of a plurality of batteries within the electronic price label, a second electrical contact for simul-

taneously providing a second electrical path to second polarity sides of the plurality of batteries, and a retainer which maintains at least a single one of the batteries in contact with the first and second electrical contacts during removal of other batteries to maintain power to the memory within the electronic price label.

FIG. 2A



## Description

**[0001]** The present invention relates to electronic price labels (EPLs), and more specifically to an electronic price label battery storage apparatus and replacement method.

**[0002]** EPL systems typically include a plurality of EPLs for merchandise items in a transaction establishment. EPLs typically display the prices of corresponding merchandise items on store shelves and are typically attached to a rail along the leading edge of the shelves. A transaction establishment may contain thousands of EPLs to display the prices of the merchandise items. The EPLs are coupled to a central server from where information about the EPLs is typically maintained in an EPL data file. Price information displayed by the EPLs is obtained from a price look-up (PLU) data file and stored within an EPL price change record.

**[0003]** EPLs further include a memory for storing information, such as serial numbers and prices. The memory is typically a volatile memory, such as random access memory (RAM). Thus, EPLs further include a power source for maintaining the contents of the memory. The power source is typically a battery.

**[0004]** However, removal and replacement of the battery causes loss of memory contents. Reprogramming the EPL with a serial number and other critical data after battery replacement is a labor intensive, error prone, and costly process.

**[0005]** Therefore, it would be desirable to provide an electronic price label battery storage apparatus and replacement method which preserve the contents of the memory during battery replacement.

**[0006]** In accordance with the teachings of the present invention, an electronic price label battery storage apparatus and replacement method is provided.

**[0007]** The electronic price label battery storage includes a first electrical contact for simultaneously providing a first electrical path to first polarity sides of a plurality of batteries within the electronic price label, a second electrical contact for simultaneously providing a second electrical path to second polarity sides of the plurality of batteries, and a retainer which maintains at least a single one of the batteries in contact with the first and second electrical contacts during removal of other batteries to maintain power to a memory within the electronic price label.

**[0008]** The method of replacing batteries in an electronic price label includes retaining at least a single one of first batteries in the electronic price label to maintain power to a memory in the electronic price label, removing a first number of the first batteries other than the single one battery from the electronic price label, and inserting a second number of second batteries into the electronic price label.

**[0009]** It is accordingly an object of the present invention to provide an electronic price label battery storage apparatus and replacement method.

**[0010]** An embodiment of the present invention will now be described, by way of example, with reference to the accompanying drawings in which:

Fig. 1 is a block diagram of an EPL including the battery storage apparatus;

Fig. 2A is a front view of the battery storage apparatus without a door;

Fig. 2B is a left side view of the battery storage apparatus without the door;

Fig. 3A is a front view of the door;

Fig. 3B is a left side view of the door;

Fig. 4A is a front view of the battery storage apparatus with the door fully closed;

Fig. 4B is a front view of the battery storage apparatus with the door partially opened to replace a first battery;

Fig. 4C is a front view of the battery storage apparatus with the door partially opened to replace a second battery; and

Fig. 5 is a perspective view of a battery storage apparatus in accordance with a second embodiment of the present invention.

**[0011]** Referring to Fig. 1, EPL 10 includes housing 28 which contains printed circuit board 26. Mounted to printed circuit board are controller 12, memory 14, communications circuitry 16, antenna 18, display 20, and battery storage apparatus 22.

**[0012]** Controller 12 controls operation of EPL 10. Controller 12 processes commands from a host system, stores display information in memory 14, and controls display of the display information in accordance with commands from the host system. Display information may include price information, promotional information, and other information a store may wish to display. Controller 12 also stores identification information during initialization of the EPL. The identification information preferably includes a serial number and any additional information which is necessary address messages to EPL 10.

**[0013]** Memory 14 stores the display information and the identification information and is preferably a volatile random access memory, such as a static random access memory (SRAM).

**[0014]** Communications circuitry 16 receives messages from the host system and returns acknowledgments to the host system.

**[0015]** Antenna 18 works with communications circuitry 16 if EPL 10 communicates wirelessly.

**[0016]** Display 20 displays display information and is preferably a liquid crystal display (LCD).

**[0017]** Battery storage apparatus 22 stores plural batteries 24. Battery storage apparatus 22 includes door 60 (Figs. 3A-3B, 4A-4C) which facilitates easy external access to batteries 24, as well as simultaneous removal of some batteries and retention of other batteries, in order to preserve the contents of memory 14.

[0018] Turning now to Figs. 2A-2B and 3A-3B, battery storage apparatus 22 is shown in more detail.

[0019] Battery storage apparatus 22 includes support member 30, battery storage well 32, door retaining portion 34, and door 60 (Figs. 3A-3B).

[0020] Support member 30 provides a foundation for battery storage well 32 and door retaining portion 34. Support member 30 may serve as a back wall of housing 28 or may be attached to an existing back wall through a mounting aperture.

[0021] Battery storage well 32 is recessed within support member 30 and has a depth sufficient to ensure that batteries 24 do not extend outside of well 32. In this manner, the outside surfaces of batteries 24 are approximately flush-mounted with the outside surface of support member 30. This design facilitates use of sliding door 60.

[0022] As illustrated, battery storage well 32 includes two battery storage chambers 36 and 38, although other designs involving additional chambers are also envisioned by the present invention. Battery storage chambers 36 and 38 are generally circular in shape and include electrical contacts 40 and 42.

[0023] In this design, electrical contact 40 contacts the inside surface of batteries 24 and is a negative contact. Electrical contact 42 contacts the sides of batteries 24 and is a positive contact. Both electrical contacts 40 and 42 have some flexibility and are normally-biased to ensure good contact is maintained with batteries 24.

[0024] Electrical contacts 40 and 42 are also designed to minimize the possibility of a short circuit condition during the battery replacement process. Electrical contact 42 is located on one side of each battery 24 which is opposite to the side being removed first. Further, removal of a battery 24 draws that battery away from electrical contact 42.

[0025] Door retaining portion 34 retains sliding door 60. Door retaining portion 34 includes upper and lower door tracks 44 and 46 and left and right door locks 48 and 50.

[0026] With reference to Fig. 2B, upper and lower door tracks 44 and 46 include inclined guide surfaces 52 and 54 which retain door 60. For this purpose, upper guide surface 52 inclines upwardly from the outer surface of upper door track 44 and lower guide surface 54 inclines downwardly from the outer surface of lower door track 46. Both upper and lower door tracks 44 and 46 are open-ended to allow door 60 to be inserted from either the left or right side and to slide in both left and right directions.

[0027] Left and right door locks 48 and 50 include spring members 52 and 54 and latches 56 and 58.

[0028] Latches 56 and 58 engage door 60 to prevent door 60 from moving left or right.

[0029] Spring members 52 and 54 connect to the center of lower door track 46. Spring members 52 and 54 bias latches 56 and 58 towards a normally-locked position, but can be bent by an application of downward

pressure on latches 56 and 58.

[0030] Advantageously, the door retaining features of the prevention invention minimize the chance of accidental opening of door 60 during handling of EPL 10 by store personnel, including dropping of EPL 10.

[0031] With reference to Figs. 3A and 3B, door 60 is generally planar and rectangular in shape. Door 60 includes inclined top and bottom edges 62 and 64. Edges 62 and 64 are inclined at angles similar to those of surfaces 52 and 54 of upper and lower door tracks 44 and 46. For this purpose, upper edge 62 inclines upwardly from outer surface 70 of door 60 and lower edge 64 inclines downwardly from outer surface 70 of door 60.

[0032] Door 60 also includes latching surfaces 66 and 68 which are generally J-shaped. Latches 56 and 58 engage latching surfaces 66 and 68 when door 60 is closed to prevent left and right movement of door 60.

[0033] Door also presses against batteries 24 to ensure good electrical contact between batteries 24 and electrical contact 40.

[0034] Referring now to Figs. 4A-4C, operation of battery storage apparatus 22 is shown in more detail. Removal and replacement of batteries 24 is accomplished by accessing and removing batteries 24 in a manner that leaves at least one battery in place during the procedure.

[0035] In Fig. 4A, door 60 is in a closed position with batteries 24A and 24B inside. Door 60 is held in the closed position by latches 56 and 58.

[0036] In Fig. 4B, latch 50 is lowered and door 60 is slid to the right to expose battery 24A. Battery 24A is removed and replaced. Door 60 is opened only about half way in order to ensure that battery 24B is still providing power during removal and replacement of battery 24A. Following replacement of battery 24A, door 60 is slid to the left, allowing latch 50 to return to its normally-biased position.

[0037] In Fig. 4C, latch 48 is lowered and door 60 is slid to the left to expose battery 24B. Battery 24B is removed and replaced. Door 60 is opened only about half way in order to ensure that battery 24A is still providing power during removal and replacement of battery 24B. Following replacement of battery 24B, door 60 is slid to the right towards a centered position, allowing latch 48 to return to its normally-biased position.

[0038] Turning now to Fig. 5, a second embodiment of battery storage apparatus 22 includes support member 80, tunnel 82, and lock 84.

[0039] Support member 80 attaches to a back surface of EPL 10. Support member 80 may serve as a back wall of housing 28 or may be attached to an existing back wall through a mounting aperture.

[0040] Battery electrical contact 86 fastens to support member 80.

[0041] Tunnel 82 extends from support member 80. Tunnel 82 is generally U-shaped and includes enough room for at least two batteries 24A and 24B. Battery

electrical contact 88 fastens to the ceiling of tunnel 82.

[0042] Lock 84 includes first and second doors which slide across tunnel 82 to simultaneously close both ends of tunnel 82.

[0043] The battery change operation begins by removing lock 84 from tunnel 82. Battery 24C is inserted into tunnel 82 at one end of tunnel 82 so as to push battery 24B out of tunnel 82 at the other end. Battery 24A remains in contact with electrical contacts 86 and 88 during sliding. Battery 24A may be removed in a similar fashion using an additional replacement battery. After batteries 24A and 24B have been pushed out of tunnel 82 by replacement batteries, lock 84 is replaced over the ends of tunnel 82.

[0044] In the first embodiment, door 60 maintains at least one of batteries 24 in place. In the second embodiment, tunnel 82 maintains at least one of batteries 24 in place.

[0045] Although the present invention has been described with particular reference to certain preferred embodiments thereof, variations and modifications of the present invention can be effected within the scope of the invention. For example, other designs including more than two batteries 24 are also envisioned by the present invention, such as a line of batteries, a matrix of batteries, or any other geometric arrangement which allows at least one battery to provide power during removal of one or more of the other batteries. Also, not all batteries need be removed and not all batteries removed need be replaced.

#### Claims

1. A battery storage apparatus in an electronic price label comprising:
  - a first electrical contact for providing a first electrical path to first polarity sides of a plurality of batteries within the electronic price label simultaneously;
  - a second electrical contact for providing a second electrical path to second polarity sides of the plurality of batteries simultaneously; and
  - a retainer which maintains at least a single one of the batteries in contact with the first and second electrical contacts during removal of other batteries to maintain power to a memory within the electronic price label.
2. An apparatus as claimed in claim 1, wherein the retainer comprises:
  - a tunnel containing the first and second electrical contacts, having a first end aperture through which a new battery is inserted, and having a second end aperture through which an old battery is ejected during insertion of the new battery.
3. An apparatus as claimed in claim 1 or claim 2, wherein the retainer comprises:
  - a plurality of battery chambers for storing the batteries, wherein the battery chambers contain the first and second electrical contacts; and
  - a door which slides across the battery chambers to expose a number of batteries for removal while retaining at least a single battery in the battery chambers to maintain power to the memory.
4. An electronic price label comprising:
  - a housing;
  - circuitry within the housing including a volatile memory; and
  - a battery storage apparatus within the housing including
    - a first electrical contact for simultaneously providing a first electrical path to first polarity sides of a plurality of batteries;
    - a second electrical contact for simultaneously providing a second electrical path to second polarity sides of the plurality of the batteries; and
    - a retainer which maintains at least a single one of the batteries in contact with the first and second electrical contacts during removal of a number of other batteries in order to maintain power to the memory.
5. An electronic price label as claimed in claim 4, wherein the retainer comprises:
  - a first sliding door adjacent the first end aperture;
  - a second sliding door adjacent the second end aperture; and
  - a linking member joining the first and second sliding doors to facilitate substantially simultaneous closure of the first and second sliding doors.
6. An electronic price label as claimed in claim 4 or claim 5, wherein the retainer comprises:
  - a plurality of battery chambers for storing the batteries, wherein the battery chambers contain the first and second electrical contacts; and
  - a door which slides across the battery chambers to expose a number of batteries for removal while retaining at least a single battery in the battery chambers to maintain power to the memory.

7. An electronic price label as claimed in any of claims 4 to 6, wherein the retainer further comprises:

a lock which maintains the door in a closed position after new batteries have been inserted in the battery chambers. 5

8. An electronic price label as claimed in claim 7, wherein the lock comprises:

a first lock member including a first spring member mounted to the housing and a first latch mounted to the first spring member which is normally biased to a position adjacent a first end of the door to prevent the door from sliding in a first direction; and 10 15

a second lock member including a second spring member mounted to the housing and a second latch mounted to the second spring member which is normally biased to a position adjacent a second end of the door to prevent the door from sliding in a second direction. 20

9. A method of replacing batteries in an electronic price label as claimed in any of claims 5 to 8 the method comprising: 25

retaining at least a single one of first batteries in the electronic price label to maintain power to a memory in the electronic price label; 30 removing a first number of the first batteries other than the single one battery from the electronic price label; and inserting a second number of second batteries into the electronic price label. 35

10. A method as claimed in of claim 9 comprising:


removing the single one battery from the electronic price label; and 40 inserting a third battery into the electronic price label.

45


50

55

FIG. 1



**FIG. 2A**









FIG. 3B





**FIG. 3A**





**FIG. 4B**




FIG. 4C






FIG. 5





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 030 240 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
11.10.2000 Bulletin 2000/41

(51) Int. Cl.<sup>7</sup>: **G06F 3/147, H01M 2/10**

(43) Date of publication A2:  
23.08.2000 Bulletin 2000/34

(21) Application number: **00300492.6**

(22) Date of filing: **24.01.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **17.02.1999 US 250858**

(71) Applicant:  
**NCR INTERNATIONAL INC.  
Dayton, Ohio 45479 (US)**

(72) Inventors:  
• **Kato, Shuzo**  
**Kanagawa 254-0902 (JP)**  
• **Utsumi, Yoshitaka**  
**Kanagawa 256-0802 (JP)**  
• **Takagi, Osamu**  
**Kanagawa 250-0055 (JP)**


(74) Representative:  
**Williamson, Brian et al**  
**International IP Department,**  
**NCR Limited,**  
**206 Marylebone Road**  
**London NW1 6LY (GB)**

(54) **Electronic price label battery storage apparatus and replacement method**

(57) An electronic price label battery storage apparatus and replacement method which maintains power to a memory within the electronic price label during removal and replacement of batteries. The battery storage apparatus includes a first electrical contact for simultaneously providing a first electrical path to first polarity sides of a plurality of batteries within the electronic price label, a second electrical contact for simul-

taneously providing a second electrical path to second polarity sides of the plurality of batteries, and a retainer which maintains at least a single one of the batteries in contact with the first and second electrical contacts during removal of other batteries to maintain power to the memory within the electronic price label.

**FIG. 2A**





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 0492

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	US 5 504 475 A (HOUDOU MICHEL ET AL) 2 April 1996 (1996-04-02) * column 1, line 10 - line 15 * * column 3, line 24 - line 33 * * column 10, line 33 - line 48 *	1-4,6,9, 10	G06F3/147 H01M2/10
Y	PATENT ABSTRACTS OF JAPAN vol. 011, no. 099 (E-493), 27 March 1987 (1987-03-27) & JP 61 250965 A (SONY CORP), 8 November 1986 (1986-11-08) * abstract *	1,2,4	
Y	PATENT ABSTRACTS OF JAPAN vol. 016, no. 475 (E-1273), 2 October 1992 (1992-10-02) -& JP 04 171655 A (MITSUBISHI ELECTRIC CORP), 18 June 1992 (1992-06-18) * abstract; figures 4,6 *	1,3,4,6, 9,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G06F H01M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 23 August 2000	Examiner Amian, D
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 02 (P04091)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 0492

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-08-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5504475 A	02-04-1996	FR 2658645 A	23-08-1991
		AU 644130 B	02-12-1993
		AU 7108091 A	22-08-1991
		CA 2036278 A	17-08-1991
		EP 0447278 A	18-09-1991
		EP 1003092 A	24-05-2000
		JP 7193882 A	28-07-1995
JP 61250965 A	08-11-1986	NONE	
JP 04171655 A	18-06-1992	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82